

## Data Sheet

Distilling / Rotary Evaporators



### RV 05 basic 2-B

Newly designed! Consisting of heating bath HB 4 basic, set of glassware RV 06.2 with vertical condenser (space-saving), drive RV 05 basic, telescopic stand RV 05.3 and boss head clamp R 271.

- Easy and jolt-free raising and lowering of the rotary evaporator
- Telescopic stand tiltable to the side
- Rodaviss screw joint allows bonded ground joints to be released easily, removable screw connections facilitate cleaning of glass components
- New condenser geometry with 1,200 cm<sup>2</sup> cooling surface, higher yield and cooler condensate constitute a contribution to environmental protection
- No chimney effect, no foaming

Accessories: RV 06.5 Evaporating flask, NS 29, RV 05.3 Telescopic stand, RV 06.6 Evaporating flask, NS 29, RV 06.7 Receiving flask, KS 35, RV 06.13 Seal, RV 06.1 Set of glassware, RV 06.2 Set of glassware, RV 06.11 Vapor tube, VC 1.1 Water jet pump, RV 06.15 Seal, VC 1.3 Magnetic solenoid valve, VC 2 IKAVAC® Vacuum controller, VC 2.4 Pump control, RV 06.4 Evaporating flask, NS 29, RV 05 basic, HB 4 basic Heating bath

Technical Data	
Type of cooling	vertical
Cooling surface [cm <sup>2</sup> ]	1200
Evaporator capacity [ml/h]	1000
Motor principle	asynchronous
Motor rating input [W]	133
Motor rating output [W]	65
Speed range [1/min]	46 - 260
Lift	manual
Stroke [mm]	190
Heating temperature range [°C]	room temp. - 225
Heat output [W]	1000
Heat control accuracy [±K]	5
Bath volume max. [l]	4
Vacuum controller integrated	no
Dimensions (W x H x D) [mm]	580 x 1000 x 480
Weight [kg]	12
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 20
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120 / 100 - 115
Frequency [Hz]	50/60
Power input [W]	1133
<b>Ident. No.</b>	<b>8018000</b>