

## Data Sheet

Distilling / Rotary Evaporators



### RV 06-ML 2-B

Consisting of heating bath HB 4 basic, set of glassware RV 06.2 with vertical condenser (space-saving), drive RV 06-ML with lift with electrical height adjustment.

- Wearless drive with brushless DC motor
- Convenience and safety with motorized lift; the glassware is not moved
- Condenser geometry with 1,200 cm<sup>2</sup> cooling surface, higher yield and cooler condensate
- No chimney effect, no foaming
- Rodaviss screw joint allows bonded ground joints to be released easily, removable screw connections facilitate cleaning of glass components

Accessories: H 11 Mains cable Euro plug, H 11 Mains cable USA plug, RV 06.5 Evaporating flask, NS 29, RV 06.4 Evaporating flask, NS 29, RV 06.6 Evaporating flask, NS 29, RV 06.7 Receiving flask, KS 35, RV 06.13 Seal, RV 06.1 Set of glassware, RV 06.2 Set of glassware, RV 06.11 Vapor tube, VC 1.1 Water jet pump, RV 06.15 Seal, VC 1.3 Magnetic solenoid valve, VC 2 IKAVAC® Vacuum controller, H 11 Mains cable UK plug, VC 2.4 Pump control, H 11 Mains cable CH plug, HB 4 basic Heating bath

Technical Data	
Type of cooling	vertical
Cooling surface [cm <sup>2</sup> ]	1200
Evaporator capacity [ml/h]	1000
Motor principle	DC
Motor rating input [W]	45
Motor rating output [W]	36
Speed range [1/min]	10 - 240
Lift	Motor
Stroke [mm]	150
Heating temperature range [°C]	room temp. - 225
Heat output [W]	1000
Heat control accuracy [±K]	5
Bath volume max. [l]	4
Vacuum controller integrated	no
Dimensions (W x H x D) [mm]	640 x 1130 x 390
Weight [kg]	18
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	1050
<b>Ident. No.</b>	<b>8010100</b>