

P-13 premium Disk Mill

# In demand wherever the going gets tough



polymer coated iron-free grinding

- feed sizes up to 20 mm depending on material
- throughput up to 150 kg/h with integrated dust extraction
- fineness down to 50 μm depending on material

- digital grinding gap adjustment for exact reproducibility
- automatic locking for utmost safety
- variable rotation clockwise and counterclockwise

## Built to handle the hard stuff

FRITSCH P-13 premium Disk Mill is in demand worldwide for medium-hard and hard-brittle samples. It sets the standard in mining, metallurgy, stone and earth, ceramics, glass, and soil research. Automatic locks on its grinding container and chamber make it user safe. It is also extremely precise and easy to operate thanks to its motorized grinding gap adjustment and digital gap display. Delivering throughput rates up to 150 kg/h, it is a proven performer.

### Easy operation meets precision grinding gap adjustment

To use P-13 premium Disk Mill, simply place your sample in its easy-to-close funnel and lock the grinding chamber at the push of a button. To set the grinding gap to an accuracy of 50  $\mu$ m, simply adjust the value using the plus and minus buttons on the unit. No cranking is required. Once you have set the grinding time to the exact second, you can start the grinding process. P-13 premium Disk Mill saves the current setting for your next grinding operation. When it comes to equalizing wear on the grinding disks or readjusting the device after an alteration, you can do this at the push of a button.



Harness the power of the Cyclone: Combine your P-13 premium Disk Mill with the powerful FRITSCH Cyclone to speed up your throughput rate and optimize grinding conditions for demanding and sensitive samples. Need advice? Get in touch!



#### Experience FRITSCH P-13 premium in action!

Watch the video to see how the intuitive user guidance makes for easy work with FRITSCH P-13 premium Disk Mill.

#### Technical data

#### P-13 premium

#### **Optimal material type**

very hard, hard-abrasive, hard-brittle, medium-hard, metal-free grinding

#### **Connection values**

400 V/3~, 50 Hz, 1,790 watts or 200 V/3~, 60 Hz, 2,100 watts

#### **Grinding disk speed**

440 rpm

#### Weight

240 kg

#### Dimensions W x D x H

Table-top appliance  $52 \times 105 \times 63 \text{ cm}$ 



#### **Contact us now**

for a non-binding consultation or test grinding to identify your ideal device configuration and parameters.

consultation@fritsch.de +49 6784 70-150



#### Find out more at

www.fritsch-international.com in the sample-preparation/milling/disk-mills

