

The Thermo Scientific Orion Star A222 Conductivity Portable Meter makes necessary testing easier. Its durability and dependability make it a great choice for samples every day, anywhere.

Thermo Scientific Orion Star A222 Conductivity Portable Meter



Get the readings that you need where you need them with the Thermo Scientific Orion Star A222 Conductivity Portable Meter. The large, backlit graphic LCD display shows conductivity/TDS/salinity/resistivity and temperature along with electrode status, time, date and calibration points.

Features and Benefits

- Anyone can use this meter with its plain language screen prompts, soft keys that update for easy selection and a multilanguage interface that supports English, Spanish, French, Italian, German and Chinese
- Don't miss a reading – AUTO-READ™ locks in the stable reading on your screen and ready indicator alerts when readings are stable
- Selectable cell constant allows for use with 2- or 4-cell conductivity cells
- Selectable reading reference temperatures of 15, 20 or 25 °C with linear or non-linear curve options
- Includes the standard practical salinity curve for salinity readings
- Linear or ISO/EN 27888 curves for TDS
- Non-volatile memory holds up to 1000 data points with time and date stamp
- Easily transfer data and keep meter software up-to-date with the USB and RS232 ports and complimentary data analysis software
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately) to use AC power
- Perfectly portable, waterproof and protected to take anywhere with a IP67-rated housing
- 3 year meter replacement warranty

Thermo Scientific Orion Star A222 Conductivity Portable Meter

Specifications



Conductivity	Range	0.001 μ S to 3000 mS
	Resolution	0.001 μ S minimum; 4 significant figures minimum
	Relative Accuracy	0.5 % reading \pm 1 digit
	Reference Temperature	15, 20, 25 $^{\circ}$ C
	Temperature Compensation	Linear (0 to 10.0 %/ $^{\circ}$ C), nLn
	Compatible Cell Constants	0.001 to 199.9
	Calibration Points	Up to 5 points
Resistivity	Range	2 ohm to 100 meg-ohm
	Resolution	2 ohms-cm
	Relative Accuracy	0.5 % reading \pm 1 digit
Salinity	Type	Practical salinity
	Range	0.01 to 80.0 ppt NaCl equivalent; 0.01 to 42 ppt practical salinity
	Resolution	0.01
	Relative Accuracy	\pm 0.1
TDS	Range	1 to 200 ppt
	Resolution	4 significant digits
	Relative Accuracy	\pm 0.5 % reading \pm 1 digit
	TDS Factor Range	Linear 0.01 to 10.00
Temperature	Range	-5 to 105 $^{\circ}$ C, 23 to 221 $^{\circ}$ F
	Resolution	0.1
	Relative Accuracy	\pm 0.1
	Offset Calibration	1 point
Datalogging	Memory	1000 with time and date stamp
	Log Function	Manual, Automatic with AUTO-READ™
	Log Edit	Delete last reading or all
Inputs	Conductivity with Temperature Probe	8-pin mini-DIN
Output		RS232, USB
Power	AC Adapter	Optional – universal, 100-240 VAC
	Battery Power	Included – 4 AAs
	Battery Life	800 hrs

Ordering Information

Cat. No.	Description
STARA2220	Orion STAR A222 Conductivity Portable Meter - Four AA batteries (installed)
STARA2225	Orion STAR A222 Conductivity Portable Meter Kit - 013010MD Orion DuraProbe conductivity cell with 3m cable, K=0.475 - 01100710 conductivity standard pouches, 1413 μ S, pack of 10 - 911110 rinse solution, pack of 10 - Protective armor with electrode holder - Hard carrying case - Four AA batteries (installed)
Accessories	
STARA-CS	Hard carrying case for Orion Star A-series portable meters
1210005	Soft carrying case for Orion Star, Star Plus and Star A-series portable meters
STARA-AR	Armor for Orion Star A-series portable meters, includes electrode holders for pH, conductivity and DO probes
STARA-ESCD	Conductivity and DO probe holder for Orion Star A-series armor
STARA-ESPH	pH electrode holder for Orion Star A-series armor
013005MD	Orion DuraProbe conductivity cell with 1.5m cable, 4-cell, K=0.475
013010MD	Orion DuraProbe conductivity cell with 3m cable, 4-cell, K=0.475
013020MD	Orion DuraProbe conductivity cell with 6m cable, 4-cell, K=0.475
013025MD	Orion DuraProbe conductivity cell with 10m cable, 4-cell, K=0.475
1010003	Optional universal power adapter, 100-240 V, 50/60 Hz
011008	Orion conductivity standard, 100 μ S/cm, 5x60 mL bottles
01100710	Orion conductivity standard pouches, 1413 μ S/cm, 10/pk
01100610	Orion conductivity standard pouches, 12.9 mS/cm, 10/pk
911110	Orion rinse solution pouches, 10/pk
1010001	Orion conductivity calibration resistor kit

For more information, contact your local Thermo Scientific products dealer or call our customer and technical service experts at 1-800-225-1480 (for the US and Canada) or visit www.thermoscientific.com/water.

©2011 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. ROSS and the COIL tradenames are trademarks of Thermo Fisher Scientific Inc. US Patent 6,793,787.



S-STARA222-E-1011-RevB

Water Analysis Instruments
www.thermoscientific.com/water

North America
166 Cummings Center
Beverly, MA 01915 USA
Toll Free: 1-800-225-1480
Tel: 1-978-232-6000
info.water@thermo.com

Netherlands
Tel: (31) 033-2463887
info.water.uk@thermo.com

China
Tel: (86) 21-68654588
wai.asia@thermofisher.com

India
Tel: (91) 22-4175-8800
wai.asia@thermofisher.com

Singapore
Tel: (65) 6778-6876
wai.asia@thermofisher.com

Japan
Tel: (81) 045-453-9175
wai.asia@thermofisher.com

Australia
Tel: (613) 9757-4300
infowaterau@thermofisher.com

Thermo
SCIENTIFIC